

## SIGNOLIT® SI 107 inkjet special film for display systems

<b>Description</b>	<i>Material</i>	- highly white rigid vinyl film with high opacity
	<i>Coating</i>	- microporous coating
	<i>Properties</i>	- scratch-resistant - can be laminated right to the edges - reduced reflections on the printed surface - brilliant colour reproduction - high opacity
	<i>Application</i>	- for indoor use
	<i>Durability</i>	- medium-term up to 12 months with pigmented inks
	<i>Printing System</i> <i>Inks</i>	- bubblejet and piezo - dye-based and pigmented inks
<b>Examples of Use</b>	<i>Indoor</i>	- posters, points of sales, pop-up displays, exhibition panels In case of a multi-panel presentation it is necessary to check before printing that in regard to the thickness of the film the printer can print with sufficient dimensional accuracy.
<b>Laminating</b>	It is necessary to protect the surface if it is subject over a long time to abrasion or any other mechanical influences, to dirt or humidity. The lamination can be done right to the edges or over the edges. The user should check before using what is more appropriate. If dye inks are used, SI 107 must be laminated indoor and outdoor to improve light-fastness and smudge-proofness. We recommend to use self-adhesive laminating foils for cold lamination.	
<b>Technical Data</b>	<i>Base material</i>	white rigid vinyl film
	<i>Thickness</i>	~ 220 µm
	<i>Grammage</i>	~ 295 g/m <sup>2</sup>
	<i>Opacity</i>	1,5
	<i>Dimensions</i>	430 mm x 20 m. 610 mm x 20 m. 914 mm x 20 m. 1067 mm x 20 m. 1270 mm x 20 m. 1520 mm x 30 m.
<b>Storage</b>	After printing the remaining roll must be removed from the plotter and stored in its closed original packing in a cool and dry environment.	
<b>Disposal</b>	The left-over pieces of film can be treated as industrial waste and incinerated. Nevertheless, it is absolutely necessary to follow the local regulations in force in the waste treatment plants.	