

DIALUX® SIFB inkjet frontprint backlit self-adhesive

Description	<i>Material</i>	- translucent self-adhesive PVC film with paper backing.
	<i>Coating</i>	- microporous coating
	<i>Properties</i>	- resistant to scratches and bending - can be laminated right to the edges - high brilliance of colours - for universal use
	<i>Application</i>	- indoor and outdoor
	<i>Durability</i>	- for outdoor use up to 12 months with pigmented inks according to DIN ISO 4892-3
	<i>Printing Systems</i> <i>Inks</i>	- bubblejet and piezo - dye-based and pigmented inks
Examples of Use	<i>Indoor and Outdoor</i>	- luminous advertising, illuminated displays, exhibition panels
Laminating	Depending on the application SIFB can also be used outdoor without lamination. However, the printed surface must be protected if it is subject over a longer period to abrasion or any other mechanical influences, to dirt or humidity. The lamination can be done right to the edges or over the edges. The user should check before using what is more appropriate. If dye inks are used, SIFB must be laminated indoor and outdoor to improve light-fastness and smudge-proofness. We recommend to use self-adhesive laminating foils for cold lamination.	
Gluing	SIFB will stick to any solid, smooth surfaces which are dry and free of dirt, grease, silicon etc. Before gluing it is absolutely necessary to check that the surface is appropriate to this aim and that it has been prepared (cleaned) professionally. During gluing the temperature must reach at least 15°C. You can remove SIFB by heating the film's surface with a hot air gun. Then pull it off carefully.	
Technical Data	<i>Base material</i>	calendered monomeric plasticized PVC
	<i>Opacity</i>	~ 0,69
	<i>Adhesive</i>	polyacrylate dispersion removable
	<i>Tackiness</i>	~ 3,2 N / 25 mm (A.F.E.R.A)
	<i>Tackiness after 24 h</i>	~ 9,0 N / 25mm (A.F.E.R.A)
	<i>Backing paper</i>	silicon paper
	<i>Thickness of paper</i>	~ 145 µm
	<i>Total thickness</i> <i>Total weight</i>	~ 300 µm ~ 305 g/m²
<i>Dimensions</i>	914 mm x 20 m. 1067 mm x 20 m. 1270 mm x 20 m.	

Storage

After printing the remaining roll must be removed from the plotter and stored in its closed original packing in a cool and dry environment.

Disposal

The left-over pieces of film can be treated as industrial waste and incinerated. Nevertheless, it is absolutely necessary to follow the local regulations in force in the waste treatment plants.

Hints

This information corresponds to our present state of knowledge and is destined to inform you without obligation about our products and their use. Our hints and recommendations do not release you from the necessity to ensure by your own tests our product's suitability for its intended use as we do not have any influence on the conditions at your place and on possible influences which may occur during use or application. Due to the large number of combinations of software options, printing profiles, printers, inks, print qualities and resolutions we cannot state exact drying times and the maximum ink quantity required. We reserve the right for any changes useful for product improvement.