

## SIGNOLIT® SI 50 OHP polyester film for inkjet

<b>Description</b>	<i>Material</i>	<ul style="list-style-type: none"> <li>- OHP polyester film for inkjet printers</li> <li>- with 10mm wide paper sensor strip glued onto short edge</li> </ul>			
	<i>Properties</i>	<ul style="list-style-type: none"> <li>- brilliant colour reproduction</li> <li>- reliable stack feeding</li> <li>- sensor strip removable without residue</li> </ul>			
	<i>Applications</i>	<ul style="list-style-type: none"> <li>- presentations, training courses</li> </ul>			
	<i>Printing Systems Inks</i>	<ul style="list-style-type: none"> <li>- bubblejet and piezo,</li> <li>- water-based dye and pigmented inks</li> </ul>			
<b>Printer Settings</b>	<i>Dependent on type</i>	<ul style="list-style-type: none"> <li>- OHP film / transparency</li> </ul>			
	<i>Feeding</i>	<ul style="list-style-type: none"> <li>- stack feed from single sheet trays</li> </ul>			
	<i>Printable side</i>	<ul style="list-style-type: none"> <li>- rough side</li> </ul>			
<b>Technical Data</b>	<i>Thickness</i>	~ 120µm			
	<i>Dimensions</i>	<table border="0"> <tr> <td>Sheets</td> <td>DIN A4 sensor strip on short edge</td> </tr> <tr> <td>Sheets</td> <td>DIN A3 without sensor strip</td> </tr> </table>	Sheets	DIN A4 sensor strip on short edge	Sheets
Sheets	DIN A4 sensor strip on short edge				
Sheets	DIN A3 without sensor strip				
<b>Storage</b>	SI 50 should be stored in its original packing at a temperature between 10°C and 32°C and at an atmospheric humidity of 30-70%.				
<b>Disposal</b>	The left-over pieces of film can be treated as industrial waste and incinerated. Nevertheless, it is absolutely necessary to follow the local regulations in force in the waste treatment plants.				