

## SIGNOLIT® SL 12 OHP polyester film for laser and copiers

<b>Description</b>	<i>Material</i>	<ul style="list-style-type: none"> <li>- OHP polyester film clear for black and white copiers and black and white laser printers</li> <li>- with paper backing glued onto long edge</li> </ul>
	<i>Properties</i>	<ul style="list-style-type: none"> <li>- excellent heat stability</li> <li>- antistatic surface</li> <li>- reliable stack feeding</li> <li>- high scratch-proofness</li> <li>- waterproof wipe clean imaged surface</li> <li>- glued paper backing removable without residue</li> </ul>
	<i>Applications</i>	<ul style="list-style-type: none"> <li>- presentations, training courses</li> </ul>
	<i>Printing Systems</i>	<ul style="list-style-type: none"> <li>- black and white laser printer</li> <li>- black and white plain paper copiers</li> <li>- black and white copiers with high output</li> </ul>
<b>Printer Settings</b>	<i>Dependent on type</i>	<ul style="list-style-type: none"> <li>- OHP film / transparency / normal paper</li> </ul>
	<i>Feeding</i>	<ul style="list-style-type: none"> <li>- stack feed from trays or single sheet feeding</li> </ul>
<b>Technical Data</b>	<i>Thickness</i>	PET film ~ 100µm
	<i>Dimensions</i>	Sheets                      DIN A4
<b>Storage</b>	SL 12 should be stored in its original packing at a temperature between 10°C and 30°C and at an atmospheric humidity of 30-70%.	
<b>Disposal</b>	The left-over pieces of film can be treated as industrial waste and incinerated. Nevertheless, it is absolutely necessary to follow the local regulations in force in the waste treatment plants.	